

NVS4

4-Channel PoE NVR for 24/7 Reliable Recording

- Support up to 16MP
- Power over Ethernet
- 4-Channel NVR
- 24/7 Continuous Recording



Specifications

Video/Audio Input	
IP Video Input	Up to 4 IP cameras
Audio Input	N/A
Video/Audio Output	
Video Out	VGA, HDMI
Display Resolution	HDMI: 3840x2160, 1920x1080, 1280x1024, 1280x720, 1024x768
	VGA: 1920x1080, 1280x1024, 1280x720, 1024x768
Audio Output	1CH RCA(add on Speaker)
Decoding	
Video Compression	H.265 / H.264
Live View/Playback Resolution	7680X2160, 4608X1728, 4512X2512, 4096X3072, 3840X2160, 2560*2560, 2560X1920, 2560X1440, 2048X1536, 2304X1296,1080P,720P
Synchronous Playback	Up to 4 channels
HDD	
SATA	1 x SATA for HDD

Capacity	Up to 6TB
External Interfaces	
USB Interface	2 x USB 2.0
Network Interface	4 x RJ-45, 10/100 Mbps self-adaptive (for IP cameras) 1 x RJ-45, 10/100 Mbps self-adaptive (for LAN/WAN)
PoE	
Max. Power per Port	25W
Supported Standard	IEEE 802.3 af/at
Network	
Network Protocols	HTTP, TCP/IP, UDP, DHCP, P2P, UPNP, RTMP, SMTP, SSL/TLS, DNS, DDNS, NTP,FTP
Browsers Supported	Edge, Firefox, Chrome, Safari
OS Supported	PC: Windows, Mac OS; Smart phone: iOS, Android
Max. User Access	20 Users (1 admin account & 19 user accounts); supports up to 12 simultaneous video streams (10 substreams & 2 mainstreams)
General	
Power Supply	DC 52V
Power Consumption	<10W (without HDD & PoE)
Working Environment	Temperature: -10°C ~ + 45°C (14°F ~ 113°F); Humidity: 10% ~ 90%
Dimensions	255mm(W) x 49.5mm(H) x 232mm(D)
Weight	1.4kg (without HDD)
Warranty	
Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/

Gallery & Specs



- ① Logo
- ② Power LED
- ③ HDD LED
- ④ Heat Dissipation Hole
- ⑤ USB Port



- ⑥ DC Port
- ⑦ On/Off Switch
- ⑧ Audio Out
- ⑨ VGA Port
- ⑩ HDMI Port
- ⑪ USB Port
- ⑫ Network
- ⑬ RJ45